



Get Expert Advice

1-888-411-RABT (7228)


[View Cart](#) | [Contact Us](#)

Find

[PRODUCTS](#) [SOLUTIONS](#) [SUPPORT](#) [COMPANY](#) [CHANNEL PARTNERS](#) [CAREERS](#) [ORDERING INFO](#)**QUICK LINKS**

- [Low-Cost Dev Kits](#)
- [Application Kits](#)
- [RabbitCores](#)
- [Latest Downloads](#)
- [Single-Board Computers](#)
- [Rabbit Support Forums](#)
- [Training/Events](#)

RCM2200 RabbitCore®

Models [RCM2200](#), [RCM2210](#), [RCM2250](#), [RCM2260](#)[RCM2200 Description](#)[RCM2200 Specifications](#)[Large View](#) | [360° View](#)

Get Rabbit eNews



Low-Cost Development Kits

Includes everything you need to begin development



Description

Our award-winning Ethernet-enabled RCM2200 RabbitCore microprocessor core module is a compact yet powerful embedded control solution for application developers working with a small design footprint. Only half the size of a credit card, the RCM2200 features the powerful [Rabbit® 2000 microprocessor](#), 256K of Flash memory, 128K of SRAM, 4 serial ports, 26 I/O, real-time clock, and integrated Ethernet. (To permit parallel development and cost-effective implementation of both Ethernet-enabled and non-Ethernet systems, our pin-compatible RCM2300 model is also available.)

Features

- Compact size (2.3" x 1.6" x 0.86")
- 10Base-T Ethernet
- Up to 512K Flash
- Up to 512K SRAM
- 26 general-purpose I/O

Designing with RabbitCores

The RabbitCore family of microprocessor core modules is designed to facilitate rapid development and implementation of embedded systems. RabbitCores are powered by high-performance 8-bit Rabbit microprocessors with extensive integrated features and a C-friendly instruction set designed for use with the [Dynamic C®](#) development system. The RabbitCore mounts on a user-designed motherboard and acts as the controlling microprocessor for the user's system. Small in size but packed with powerful features, these core modules give designers a complete package for control and communication.

The integrated Ethernet port frees designers from the limitations of serial-port communications and control and also permits instant local or worldwide connectivity using low-cost networking hardware. Embedded systems using the Ethernet RabbitCore module can be controlled and monitored (as well as programmed and debugged when using appropriate accessory hardware) across any network or the Internet.

RCM2200 CoreModule Specifications

Features	RCM2200	RCM2210	RCM2250	RCM2260
Microprocessor		Rabbit 2000T at 22.1 MHz		
Ethernet Port	10Base-T, RJ-45, 2 LEDs	10Base-T (raw signals only)	10Base-T, RJ-45, 2 LEDs	10Base-T, (raw signals only)
Flash		256K		512K
SRAM		128K		512K
Backup Battery	Connection for user-supplied battery (to support RTC and SRAM)			
General Purpose I/O	26 parallel I/O include: <ul style="list-style-type: none"> • 16 configurable I/O • 7 fixed inputs • 3 fixed outputs 			
Additional Inputs	2 Startup Mode, Reset			
Additional Outputs	Status, Reset			
Memory I/O	4 address, 8 data, plus I/O Read-Write			
Serial Ports	Four 5 V CMOS-compatible, 2 configurable as clocked ports (1 clocked line available only on programming header)			
Serial Rate	Max. burst rate = CLK/32 Max. sustained rate = burst/2			
Connectors	Two 2 x 13, 2 mm IDC headers			
Slave Interface	Slave port permits use as master or as intelligent peripheral with other master controller			
Real-Time Clock	Yes			
Timers	Five 8-bit timers (four cascadable from the first) and one 10-bit timer with 2 match registers			
Watchdog/Supervisor	Yes			
Power	4.75-5.25 V DC, 134 mA			
Operating Temp.	-40°C to +70°C			
Humidity	5-95%, non-condensing			
Board Size	2.3" x 1.6" x 0.86" (59 mm x 41 mm x 22 mm)			
Part Number	20-101-0454	20-101-0488	20-101-0494	20-101-0955
Development Kit	U.S. 101-0475, Int'l 101-0476			

[Site Map](#) | [Privacy Policy](#) | [Contact Us](#) | [Feedback](#)

Copyright © 2008 Rabbit All Rights Reserved A Digi International® Brand