



- NOTES:**
1. INSERTION LOSS: 0.25 dB MAX.
 2. OPERATION TEMP: -40°C TO +80°C.
 3. MATERIALS:
 ST2 ADAPTER:
 BODY - ZINC ALLOY
 RETENTION WASHER - BRASS, NICKEL PLATED
 SLEEVE - CERAMIC, SINGLE-MODE
 - COPPER ALLOY, MULTI-MODE
 DUST CAPS - PVC
 NUT - COPPER ALLOY, NICKEL PLATED
 LOCKWASHER - STEEL, NICKEL PLATED
 FLANGE - ZINC ALLOY
 4. THIS PRODUCT IS RoHS COMPLIANT.

PART NUMBER	ST2 ADAPTER SEE NOTE 3	DUST CAP COLOR	FLANGE FINISH
EHST2	SINGLE-MODE	RED	NICKEL
EHST2M	DOUBLE-MODE	BLACK	NICKEL
EHST2B	SINGLE-MODE	RED	BLACK CHROME
EHST2MB	DOUBLE MODE	BLACK	BLACK CHROME

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 1.5:1		
B	27621	12-4-15	TO	TJK	DATE DRAWN	BY	CHKD	APVD	Switchcraft®
A	26306	12/1/08	RS	TJK	5/12/08	JGK	RS	6/2/09	
					SHEET 1 OF 1				
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.	REV
REVISIONS					E SERIES ST2 FIBER OPTIC ADAPTER, RoHS			EHST2_SERIES	B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Switchcraft:](#)

[EHST2M](#) [EHST2](#) [EHST2MB](#) [EHST2B](#)