


IC0-320-CTT



IC0-624-MGT

(2,54mm) .100"

IC0 SERIES

LOW PROFILE OPEN BODY DIP SOCKETS

Mates with:
APA

IC0	ROW SPACING & NO. OF CONTACTS	STYLE OPTION	PLATING OPTION	OPTION (Leave Blank for Standard Version)																												
Specify from chart below																																
<ul style="list-style-type: none"> Low profile down to (2,11mm) .083" above printed circuit board Side & end stackable Open body design Surface mountable lead sockets 																																
		<table border="1"> <thead> <tr> <th></th> <th>Row Space</th> <th>Contacts</th> </tr> </thead> <tbody> <tr><td>-308</td><td rowspan="6">.300 (7,62)</td><td>08</td></tr> <tr><td>-314</td><td>14</td></tr> <tr><td>-316</td><td>16</td></tr> <tr><td>-318</td><td>18</td></tr> <tr><td>-320</td><td>20</td></tr> <tr><td>-322</td><td>22</td></tr> <tr><td>-324</td><td>.400 (10,16)</td><td>24</td></tr> <tr><td>-422</td><td rowspan="4">.600 (15,24)</td><td>24</td></tr> <tr><td>-624</td><td>28</td></tr> <tr><td>-632</td><td>32</td></tr> <tr><td>-640</td><td>40</td></tr> </tbody> </table>		Row Space	Contacts	-308	.300 (7,62)	08	-314	14	-316	16	-318	18	-320	20	-322	22	-324	.400 (10,16)	24	-422	.600 (15,24)	24	-624	28	-632	32	-640	40	<p>GG = 30µ" (0,76µm) Gold Contact, 10µ" (0,25µm) Gold Shell</p> <p>GT = 30µ" (0,76µm) Gold Contact, Tin Shell</p> <p>TT = Tin Contact and Shell (-C, -S, -ZS, -A, -L, -M, -N, only)</p> <p>ST = 10µ" (0,25µm) Gold Contact, Tin Shell (Styles -S & -ZS only)</p>	<p>-L = Locking Socket</p> <p>Requires Style -S, -ZS or -P and (0,89mm) .035" ± (0,08mm) .003" board hole.</p> <p>Requires GT Plating Option</p>
	Row Space	Contacts																														
-308	.300 (7,62)	08																														
-314		14																														
-316		16																														
-318		18																														
-320		20																														
-322		22																														
-324	.400 (10,16)	24																														
-422	.600 (15,24)	24																														
-624		28																														
-632		32																														
-640		40																														

SPECIFICATIONS

For complete specifications see www.samtec.com?IC0

Insulator Material: Black Glass Filled Polyester
Contact: BeCu
Shell: Brass except style K Phosphor Bronze
Plating: Au or Sn over 50µ" (1,27µm) Ni
Flammability Rating: UL 94V-O
Insulation Resistance: 5000 MΩ min
Temperature Range: -55°C to +125°C with Gold -55°C to +105°C with Tin
Withstanding Voltage: 1000 VRMS @ 60 Hz
Current Rating: 1A
Contact Resistance: 10mΩ max
Lead Size Range: (0,38mm) .015" to (0,56mm) .022" DIA and most IC leads except C, L, M, and N
Insertion Force: (Single Contact only) Standard = 9 oz avg, 16 oz max; Low Insertion Force = 2.5 oz avg, 5.5 oz max
Withdrawal Force: (Single Contact only) Standard = 2.5 oz avg, 1.5 oz min; Low Insertion Force = 2.0 oz avg, 0.35 oz min except
Lead-Free Solderable: Wave only
RoHS Compliant: Yes

Note: Some sizes, styles and options are non-standard, non-returnable.

-L = Low Profile	-M = Low Profile For LIF Specify -ZM	-N = Micro Socket												
<p>Lead DIA Accepted = (0,38mm) .015" to (0,51mm) .020"</p>	<p>Lead DIA Accepted = (0,41mm) .016" to (0,53mm) .021"</p>	<p>Lead DIA Accepted = (0,41mm) .016" to (0,51mm) .020"</p>												
-C = Micro Socket For LIF Specify -ZC	-S, -ZS, -ZA = Printed Circuit -ZS & -ZA= Low Insertion Force													
<p>Lead DIA Accepted = (0,41mm) .016" to (0,51mm) .020"</p>	<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>X DIA</th> <th>Y TAIL</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>-S or -ZS</td> <td>(0,51) .020</td> <td>(3,18) .125</td> <td>(7,62) .300</td> </tr> <tr> <td>-ZA</td> <td>(0,51) .020</td> <td>(4,57) .180</td> <td>(8,89) .350</td> </tr> </tbody> </table> <p>Locking lead (-L) available. See OPTION.</p>		LEAD STYLE	X DIA	Y TAIL	Z	-S or -ZS	(0,51) .020	(3,18) .125	(7,62) .300	-ZA	(0,51) .020	(4,57) .180	(8,89) .350
LEAD STYLE	X DIA	Y TAIL	Z											
-S or -ZS	(0,51) .020	(3,18) .125	(7,62) .300											
-ZA	(0,51) .020	(4,57) .180	(8,89) .350											

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[ICO-628-NGT](#) [ICO-316-SGT](#) [ICO-320-SGT](#) [ICO-628-SGT](#) [ICO-308-STT](#) [ICO-316-NGT](#) [ICO-314-SGT](#) [ICO-640-SGT](#) [ICO-308-SGT](#) [ICO-628-MGT](#) [ICO-624-ZSGG](#) [ICO-628-SST](#) [ICO-632-AGT](#) [ICO-632-ZLGG](#) [ICO-640-LTT](#) [ICO-640-ZSTT](#) [ICO-324-MGT](#) [ICO-324-SST](#) [ICO-324-ZLGG](#) [ICO-422-MTT](#) [ICO-422-ZSST](#) [ICO-624-MTT](#) [ICO-624-ZSGT](#) [ICO-628-AGT](#) [ICO-628-CTT](#) [ICO-628-SGT-L](#) [ICO-628-STT](#) [ICO-628-ZCGT](#) [ICO-628-ZNGG](#) [ICO-628-ZSST](#) [ICO-632-MGG](#) [ICO-632-ZCGT](#) [ICO-640-LGT](#) [ICO-648-SST](#) [ICO-324-ZAGT](#) [ICO-324-ZCGT](#) [ICO-422-LGG](#) [ICO-422-ZAGG](#) [ICO-422-ZCGT](#) [ICO-422-ZMGT](#) [ICO-624-LTT](#) [ICO-624-MGT](#) [ICO-624-ZLGT](#) [ICO-628-KGT](#) [ICO-632-ATT](#) [ICO-632-CGT](#) [ICO-632-STT](#) [ICO-632-ZAGG](#) [ICO-632-ZAGT](#) [ICO-640-CGT](#) [ICO-640-STT](#) [ICO-640-STT-L](#) [ICO-648-NGT](#) [ICO-648-SGT](#) [ICO-422-SGG](#) [ICO-624-AGT](#) [ICO-624-CGG](#) [ICO-624-ZSTT](#) [ICO-628-AGG](#) [ICO-628-ZSGG](#) [ICO-628-ZSGT](#) [ICO-632-MTT](#) [ICO-632-NTT](#) [ICO-632-ZMGT](#) [ICO-640-MGT](#) [ICO-640-ZMGG](#) [ICO-640-ZMGT](#) [ICO-640-ZNGT](#) [ICO-640-ZSGG](#) [ICO-640-NTT](#) [ICO-640-ZCGG](#) [ICO-640-ZLGT](#) [ICO-640-ZSST](#) [ICO-320-KGT](#) [ICO-320-ZAGG](#) [ICO-320-ZAGT](#) [ICO-320-ZCGG](#) [ICO-322-LGT](#) [ICO-322-MGG](#) [ICO-322-MTT](#) [ICO-324-CTT](#) [ICO-324-KGT](#) [ICO-422-CGT](#) [ICO-422-CTT](#) [ICO-624-LGT](#) [ICO-624-ZLGG](#) [ICO-624-ZMGT](#) [ICO-628-JGG](#) [ICO-628-LGG](#) [ICO-628-ZAGT](#) [ICO-628-ZCGG](#) [ICO-632-CTT](#) [ICO-640-JGG](#) [ICO-640-KGT](#) [ICO-640-SST](#) [ICO-322-LGG](#) [ICO-322-NGT](#) [ICO-324-LGT](#) [ICO-422-CGG](#) [ICO-624-CTT](#)